



5AS4

5AS4

### FULL-WAVE VACUUM RECTIFIER

#### GENERAL DATA

##### Electrical:

Filament, Coated:

Voltage . . . . . 5 . . . . . ac volts  
 Current . . . . . 3 . . . . . amp

##### Mechanical:


Mounting Position . . . . . Vertical, base up or down, or  
 Horizontal with pins 1 and 4 in vertical plane  
 Maximum Overall Length . . . . . 5-1/8"  
 Maximum Seated Length . . . . . 4-9/16"  
 Maximum Diameter . . . . . 2-1/16"  
 Bulb . . . . . ST-16  
 Base . . . . . Medium-Shell Octal 8-Pin (JETEC No. B8-11),  
 or Medium-Shell Octal 5-Pin (JETEC No. B5-15)  
 Basing Designation for BOTTOM VIEW . . . . . 5T

Pin 1 - No Connection

Pin 2 - Filament

Pin 3 - Same as Pin 1

Pin 4 - Plate No. 2



Pin 5 - Same as Pin 1

Pin 6 - Plate No. 1

Pin 7 - Same as Pin 1

Pin 8 - Filament

**MAXIMUM RATINGS, TYPICAL OPERATION, and CURVES**  
 for Type 5AS4 are the same as those shown for Type 5U4-GB

